

FOUNDATION FOR INTELLIGENT PHYSICAL AGENTS

FIPA Nomadic Application Support Ontology Specification

Document title	FIPA Nomadic Application Support Ontology Specification		
Document number	OC00065C	Document source	FIPA Nomadic Application Support
Document status	Obsolete	Date of this status	2001/08/10
Supersedes	None		
Contact	fab@fipa.org		
Change history			
2000/08/04	Document made obsolete by FIPA00014		
2001/08/10	Line numbering added		

© 2000 Foundation for Intelligent Physical Agents - <http://www.fipa.org/>

Geneva, Switzerland

Notice

Use of the technologies described in this specification may infringe patents, copyrights or other intellectual property rights of FIPA Members and non-members. Nothing in this specification should be construed as granting permission to use any of the technologies described. Anyone planning to make use of technology covered by the intellectual property rights of others should first obtain permission from the holder(s) of the rights. FIPA strongly encourages anyone implementing any part of this specification to determine first whether part(s) sought to be implemented are covered by the intellectual property of others, and, if so, to obtain appropriate licenses or other permission from the holder(s) of such intellectual property prior to implementation. This specification is subject to change without notice. Neither FIPA nor any of its Members accept any responsibility whatsoever for damages or liability, direct or consequential, which may result from the use of this specification.

19 **Foreword**

20 The Foundation for Intelligent Physical Agents (FIPA) is an international organization that is dedicated to promoting the
21 industry of intelligent agents by openly developing specifications supporting interoperability among agents and agent-
22 based applications. This occurs through open collaboration among its member organizations, which are companies and
23 universities that are active in the field of agents. FIPA makes the results of its activities available to all interested parties
24 and intends to contribute its results to the appropriate formal standards bodies.

25 The members of FIPA are individually and collectively committed to open competition in the development of agent-
26 based applications, services and equipment. Membership in FIPA is open to any corporation and individual firm,
27 partnership, governmental body or international organization without restriction. In particular, members are not bound to
28 implement or use specific agent-based standards, recommendations and FIPA specifications by virtue of their
29 participation in FIPA.

30 The FIPA specifications are developed through direct involvement of the FIPA membership. The status of a
31 specification can be either Preliminary, Experimental, Standard, Deprecated or Obsolete. More detail about the process
32 of specification may be found in the FIPA Procedures for Technical Work. A complete overview of the FIPA
33 specifications and their current status may be found in the FIPA List of Specifications. A list of terms and abbreviations
34 used in the FIPA specifications may be found in the FIPA Glossary.

35 FIPA is a non-profit association registered in Geneva, Switzerland. As of January 2000, the 56 members of FIPA
36 represented 17 countries worldwide. Further information about FIPA as an organization, membership information, FIPA
37 specifications and upcoming meetings may be found at <http://www.fipa.org/>.

38 **Contents**

39	1	Scope	1
40	2	Nomadic Application Support Ontology	2
41	2.1	Object Descriptions.....	2
42	2.1.1	Quality of Service Description	2
43	2.1.2	Rate Value	3
44	2.1.3	Time Value	4
45	2.1.4	Probability Value.....	4
46	2.1.5	Change Constraint.....	4
47	2.1.6	Time Constraint	5
48	2.1.7	Communication Channel Description	5
49	2.1.8	Transport Protocol Description	5
50	2.1.9	Transport Protocol Selection	6
51	2.2	Exceptions	6
52	2.2.1	Not Understood Exception Propositions.....	6
53	2.2.2	Refusal Exception Propositions.....	6
54	2.2.3	Failure Exception Propositions	7
55	3	Message Representation Ontology.....	8
56	3.1	Object Descriptions.....	8
57	3.1.1	Message Representation Description.....	8
58	3.1.2	Message Representation Selection.....	8
59	4	References.....	9
60			

60 **1 Scope**

61 This document is part of the FIPA specifications and deals with agent middleware to support applications in nomadic
62 environment. This specification also forms part of the FIPA Nomadic Application Support Specification [FIPA00066] and
63 contains specifications for:

64

65 Ontological descriptions.

66

66 2 Nomadic Application Support Ontology

67 2.1 Object Descriptions

68 This section describes a set of frames that represent the classes of objects in the domain of discourse within the
69 framework of the FIPA-Nomadic-Application and FIPA-MTS-QoS ontologies.

70
71 The following terms are used to describe the objects of the domain:

72
73 **Frame.** This is the mandatory name of this entity that must be used to represent each instance of this class.

74
75 **Ontology.** This is the name of the ontology, whose domain of discourse includes the parameters described in the
76 table.

77
78 **Parameter.** This is the mandatory name of a parameter of this frame.

79
80 **Description.** This is a natural language description of the semantics of each parameter.

81
82 **Presence.** This indicates whether each parameter is mandatory or optional.

83
84 **Type.** This is the type of the values of the parameter: Integer, Word, String, URL, Term, Set or Sequence.

85
86 **Reserved Values.** This is a list of FIPA-defined constants that can assume values for this parameter.

88 2.1.1 Quality of Service Description

89 This type of object represents the quality of service of the transport protocol.

90

Frame Ontologies	qos FIPA-Nomadic-Application FIPA-MTS-QoS	Parameter	Description	Presence	Type	Reserved Values
line-rate	The bandwidth in one direction over the link.	Optional ¹	rate-value			
throughput	The number of user data bits successfully transferred in one direction across the link ² . Successful transfer means that no user data bits are lost, added or inverted in transfer.	Optional	rate-value			
throughput-std-dev	The current standard deviation of the throughput within a time unit.	Optional	rate-value			
rtt	The round trip time, which is the time, required for a data segment to be transmitted to a peer entity and a corresponding acknowledgement sent back to the originating entity.	Optional	time-value			
rtt-std-dev	The standard deviation of the round-trip time within a time unit.	Optional	time-value			
delay	The (nominal) time required for a data segment to be transmitted	Optional	time-value			

¹ While all of the parameters for this object are optional, a valid qos object will contain at least one parameter.

² See [ITUX135].

	to a peer entity.			
delay-std-dev	The standard deviation of the delay time within a time unit.	Optional	time-value	
mean-up-time	The expected uptime of an established link.	Optional	time-value	
omission-rate	The probability that a data segment is not transmitted correctly over a link.	Optional	probability-value	
ber	The ratio of the number of bit errors to the total number of bits transmitted in a given time interval ³ .	Optional	probability-value	
frame-error-rate	The probability that a data segment is not transmitted correctly over a link.	Optional	probability-value	
conn-setup-delay	The (sampled) delay to establish a connection between communicating entities.	Optional	time-value	
conn-setup-failure-prob	The ratio of total call attempts that result in call setup failure to the total call attempts in a population of interest.	Optional	probability-value	
status	The connectivity status of the link.	Optional	Word	Connected Disconnected Connecting

91

92 **2.1.2 Rate Value**

93 This type of object represents a data transfer value.

94

Frame Ontologies	rate-value FIPA-Nomadic-Application FIPA-MTS-QoS			
Parameter	Description	Presence	Type	Reserved Values
direction	The direction in which this value is measured.	Mandatory	Word	Inbound Outbound
unit	The unit in which the value is represented.	Mandatory	Word	GBits/s MBits/s KBits/s Bits/s
value	The rate value.	Mandatory	Number	

95

³ See [ITUE00].

95 **2.1.3 Time Value**

96 This type of object represents a time value.

97

Frame Ontologies	time-value FIPA-Nomadic-Application FIPA-MTS-QoS			
Parameter	Description	Presence	Type	Reserved Values
direction	The direction in which this value is measured.	Optional ⁴	Word	Inbound Outbound
unit	The unit in which the value is represented.	Mandatory	Word	h m s ms
value	The time value.	Mandatory	Number	

98

99 **2.1.4 Probability Value**

100 This type of object represents a probability value.

101

Frame Ontologies	probability-value FIPA-Nomadic-Application FIPA-MTS-QoS			
Parameter	Description	Presence	Type	Reserved Values
direction	The direction in which this value is measured.	Optional	Word	Inbound Outbound
value	The probability value which obeys the following axiom: $0 \bullet \text{value} \bullet 1$	Mandatory	Number	

102

103 **2.1.5 Change Constraint**

104 This type of object represents constraints that limit quality of service notifications (see [FIPA00062]).

105

Frame Ontologies	change-constraint FIPA-Nomadic-Application FIPA-MTS-QoS			
Parameter	Description	Presence	Type	Reserved Values
value	The description of the constraints.	Mandatory	Expression	

106

107

⁴ This parameter is mandatory for those quality of service values that have a different value depending upon the direction.

107 **2.1.6 Time Constraint**

108 This type of object represents constraints that limit quality of service notifications.

109

Frame Ontologies	time-constraint FIPA-Nomadic-Application FIPA-MTS-QoS			
Parameter	Description	Presence	Type	Reserved Values
type	The type of the constraint. If the type <code>Every</code> is used, then the expression becomes true after <code>value</code> and thereafter at intervals of <code>value</code> . If the type <code>After</code> is used, then the expression becomes true only after <code>value</code> .	Mandatory	Word	Every After
value	The time value.	Mandatory	time-value	

110

111 **2.1.7 Communication Channel Description**

112 This type of object represents a communication channel.

113

Frame Ontologies	comm-channel FIPA-Nomadic-Application FIPA-Communication-Management			
Parameter	Description	Presence	Type	Reserved Values
name	The logical name of the communication channel.	Optional ⁵	Word	
target-addr	The target transport address of the communication channel. This may also be the address of a gateway ACC.	Optional	URL	
options	A list of optional parameters for the communication channel.	Optional	Set of property (see [FIPA00023])	

114

115 **2.1.8 Transport Protocol Description**

116 This type of object represents a transport protocol.

117

Frame Ontologies	transport-protocol FIPA-Nomadic-Application FIPA-Communication-Management			
Parameter	Description	Presence	Type	Reserved Values
name	The logical name of the transport protocol.	Mandatory	Word	See [FIPA00074]
gw-addr	The transport address of the gateway ACC.	Optional	URL	
dest-addr	The transport address of the ultimate destination. If this address is present, but <code>gw-addr</code> is not, then the Control Agent may select the most appropriate gateway transport address to use.	Optional	URL	
options	A list of optional parameters for the transport protocol.	Optional	Set of property	

⁵ Either the `:name` parameter or the `:target-addr` parameter must be present in this object.

118 **2.1.9 Transport Protocol Selection**

119 This type of object represents a selection of transport protocol.

120

Frame Ontologies	transports FIPA-Nomadic-Application FIPA-Communication-Management			
Parameter	Description	Presence	Type	Reserved Values
send	A list of transport protocols supported for sending messages.	Mandatory	Sequence of transport-protocol	
recv	A list of transport protocols supported for receiving messages.	Mandatory	Sequence of transport-protocol	

121

122 **2.2 Exceptions**123 The exceptions for the FIPA-Nomadic-Application ontology follow the same form and rules as specified in
124 [FIPA00023].

125

126 **2.2.1 Not Understood Exception Propositions**

Communicative Act Ontology	not-understood FIPA-Nomadic-Application	
Predicate Symbol	Arguments	Description
unsupported-act	String	The receiving agent does not support the specific communicative act; the string identifies the unsupported communicative act.
unexpected-act	String	The receiving agent supports the specified communicative act, but it is out of context; the string identifies the unexpected communicative act.
unsupported-value	String	The receiving agent does not support the value of a message parameter; the string identifies the message parameter name.
unrecognised-value	String	The receiving agent cannot recognise the value of a message parameter; the string identifies the message parameter name.

127

128 **2.2.2 Refusal Exception Propositions**

Communicative Act Ontology	refuse FIPA-Nomadic-Application	
Predicate symbol	Arguments	Description
unauthorised		The sending agent is not authorised to perform the function.
unsupported-function	String	The receiving agent does not support the function; the string identifies the unsupported function name.
missing-argument	String	A mandatory function argument is missing; the string identifies the missing function argument name.
unexpected-argument	String	A mandatory function argument is present which is not required; the string identifies the unrequired function argument.

unexpected-argument-count		The number of function arguments is incorrect.
missing-parameter	String String	A mandatory parameter is missing; the first string represents the object name and the second string identifies the missing parameter name.
unexpected-parameter	String String	The receiving agent does not support the parameter; the first string represents the function name and the second string identifies the unsupported parameter name.
unrecognised-parameter-value	String String	The receiving agent cannot recognise the value of a parameter; the first string represents the object name and the second string identifies the parameter name of the unrecognised parameter value.
already-open	String	The specified communication channel is already open; the string identifies the communication channel.
not-open	String	The specified communication channel is not open; the string identifies the communication channel.
already-activated	String	The specified transport protocol is already activated; the string identifies the transport protocol.
not-active	String	The specified transport protocol is not active; the string identifies the transport protocol.
unrecognised-comm-channel	String	The specified communication channel is not recognised; the string identifies the communication channel.
unsupported-protocol	String	The specified transport protocol is not supported; the string identifies the transport protocol.

129

130 **2.2.3 Failure Exception Propositions**

Communicative Act Ontology	failure FIPA-Agent-Management	
Predicate symbol	Arguments	Description
internal-error	String	An internal error occurred; the string identifies the internal error.
open-failed	String	The opening of a communication channel failed; the string identifies the failure reason.
transient-failed	String	The opening/closing of a communication channel or the activation/deactivation of a transport protocol failed; the string identifies the failure reason.
close-failed	String	The closing of a communication channel failed; the string identifies the failure reason.
activation-failed	String	The activation of a transport protocol failed; the string identifies the failure reason.
deactivation-failed	String	The deactivation of a transport protocol failed; the string identifies the failure reason.

131

132

132 **3 Message Representation Ontology**

133 **3.1 Object Descriptions**

134 This section describes a set of frames that represent the classes of objects in the domain of discourse within the
 135 framework of the FIPA-Message-Representation ontology.
 136

137 **3.1.1 Message Representation Description**

138 This type of object represents an ACL message representation.
 139

Frame Ontologies	msg-representation FIPA-Message-Representation			
Parameter	Description	Presence	Type	Reserved Values
name	The name of the message representation.	Mandatory	Word	See [FIPA00068]
options	A list of parameters for the message representation.	Optional	Set of property	

140

141 **3.1.2 Message Representation Selection**

142 This type of object represents a selection of message representations.
 143

Frame Ontologies	msg-rep-selection FIPA-Message-Representation			
Parameter	Description	Presence	Type	Reserved Values
send	A list of message representations supported for sending messages.	Mandatory	Sequence of msg-representation	
recv	A list of message representations supported for receiving messages.	Mandatory	Sequence of msg-representation	

144

145

146

146 4 References

- 147 [FIPA00023] FIPA Agent Management Specification. Foundation for Intelligent Physical Agents, 2000.
148 <http://www.fipa.org/specs/fipa00023/>
- 149 [FIPA00062] FIPA Nomadic Application Support Monitor Agent Specification. Foundation for Intelligent Physical
150 Agents, 2000. <http://www.fipa.org/specs/fipa00062/>
- 151 [FIPA00066] FIPA Nomadic Application Support Specification. Foundation for Intelligent Physical Agents, 2000.
152 <http://www.fipa.org/specs/fipa00066/>
- 153 [FIPA00068] FIPA ACL Message Representation Library Specification. Foundation for Intelligent Physical Agents,
154 2000. <http://www.fipa.org/specs/fipa00068/>
- 155 [FIPA00074] FIPA Agent Message Transport Protocol Library Specification. Foundation for Intelligent Physical
156 Agents, 2000. <http://www.fipa.org/specs/fipa00074/>
- 157 [ITUE800] Recommendation E.800 - Telephone Network and ISDN, Quality of Service, Network Management and
158 Traffic Engineering, Terms and Definitions Related to Quality of Service and Network Performance
159 Including Dependability. International Telecommunication Union, International Telecommunication
160 Union, 1995.
- 161 [ITUX135] Recommendation X.135 - Speed of Service (delay and throughput), Performance Values for Public
162 Data Networks when Providing Packet-Switched Services. International Telegraph and Telephone
163 Consultative Committee, 1993.